

MSDS 0091244

Print

Go Back

All MSDS

9124-4: Silicone Spray Lubricant [12]

MSDS Last updated: 01/11/2012

N-1015494A

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585
 Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 116DA SILICONE SPRAY LUBRICANT
 10.25OZ AE
 80070
 Aerosol Lubricant

Item No:
 Product Type:

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER	>60	Not listed	Not listed
7732-18-5 DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	<25	Not listed	Not listed
64742-47-8 BUTANE	<20	1000 ppm	800 ppm; 1900 mg/m ³
106-97-8 PROPANE	<10	1000 ppm	1000 ppm; 1800 mg/m ³
74-98-6 POLYDIMETHYLSILOXANE	<5	Not listed	Not listed
63148-62-9			

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Excessive inhalation causes headache, dizziness, nausea, and incoordination. Aspiration if swallowed.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Overexposure may cause eye and skin redness.

Medical Conditions Recognized as Being Aggravated by Exposure: None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F (C°): Flammable - Based on flame projection test
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers cool.
Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Do not puncture or incinerate container. Do not use near heat, sparks or open flame. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid
Odor: Petroleum distillates
Boiling Point: >300°F
pH: Not determined
Solubility in Water: Forms an insoluble emulsion.
Specific Gravity: 0.93-0.97
VOC (Wt.%): 20% by weight; 1.44 lb/gal; 173.08 g/l
Vapor Pressure: Not determined
Vapor Density (Air=1): Heavier than air
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur.
Incompatibilities: Strong oxidizers

Conditions to Avoid: Keep away from heat, sparks and open flame. -
No smoking.

Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D0001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name: Consumer Commodity

Hazard Class: ORM-D

UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity

Hazard Class: Class 2.1

UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) are listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 2, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 2, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: May 27, 2009

Company: Permatex, Inc. 10 Columbus Revision 3

Blvd. Hartford, CT USA Number:
06106

Telephone No.: 1-87-Permatex (877) 376-2839

The information contained in this MSDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of Imperial Supplies LLC, Imperial will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this 'dfmt' shall be created or inferred by any statement in this 'dfmt'. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this 'dfmt'. The user is responsible for full compliance.